AQUELON HYDRATION · WALL FOUNTAINS

Murdock A132400S-VR

Bi-level wall mounted drinking fountain, vandal resistant, with 32 inch trim panel



A barrier free, vandal resistant, bi-level wall mounted drinking fountain in 18 gauge, 304 stainless steel with a brushed finish. Two piece contoured bowls with integral P-traps, chrome plated brass push buttons and polished stainless steel non-squirt bubblers. Murdock rates it for indoor and outdoor use.

KEY FEATURES

- Two bowls at adult and child heights, ADA compliant when properly installed
- 18 gauge, 304 stainless steel basins with a brushed finish
- Polished stainless steel bubblers: vandal resistant, anti-rotation and non-squirt
- Chrome plated brass push buttons, under 5 lbf (about 22 N) to operate
- Integral P-traps and a 100 mesh inlet strainer

SPECIFICATIONS

Model shown	A132400S-VR: lead-free stainless steel bubbler, satin stainless finish
Mounting	Wall mounted, bi-level, with 32 inch trim panel, mounting plate A0000000-MP2-W32 and vandal resistant screws
Basin material	18 gauge, 304 stainless steel, brushed finish
Bubbler	Polished stainless steel, vandal resistant, anti-rotation, non-squirt
Activation	Chrome plated brass push button, less than 5 lbf (about 22 N)
Water pressure range	20 to 105 psig (about 1.4 to 7.2 bar)
Inlet	100 mesh inlet strainer, auto-stop for service
Waste	P-traps integral to the unit
Trim panel	32 in [813 mm] wide, 20 in [509 mm] high
Projection from wall	18 1/2 in [469 mm]

Manufactured by Murdock. Supplied in the GCC by Aquelon. Data from the manufacturer's published documentation, issued 17 November 2026; confirm against the manufacturer's current data and drawings before construction or ordering. Source: Murdock manufacturer documentation

Bowl spacing	16 in [407 mm] between bowl centres
Mounting height	Murdock's drawing shows 33 in [838 mm] to the lower unit for the recommended adult height. Adjust to the codes that apply on site
Use	Rated by Murdock for indoor and outdoor use
Tolerance	Dimensions plus or minus 1/4 in nominal, per Murdock
Mounting carrier	Compatible with Jay R. Smith Mfg. Co. Figure 0824

OPTIONS

- Flexible bubbler (low flow): A132200F-VR bronze, A132300F-VR gold (high polish), A132400F-VR satin stainless
- Lead-free stainless steel bubbler: A132200S-VR bronze, A132300S-VR gold (high polish), A132400S-VR satin stainless
- -HP high polished stainless steel
- -RBL reverse bi-level
- -SK4-18 stainless steel skirt kit for the upper unit
- -WF3000 PFAS water filter, 3,000 gallon (about 11,350 litre) capacity, located remotely by the installer
- A9100080-A remote water chiller, 8 gallons (about 30 litres) an hour, recommended within 10 ft (3 m) of the fixture

STANDARDS AND CERTIFICATIONS

- US Federal Public Law 111-380 (no lead)
- NSF/ANSI/CAN 61-2020
- Meets ADA, ADA standing person and ADA child requirements when mounted appropriately (US accessibility standard)
- WF3000 filter: third party certified for lead, bacteria, chlorine and microplastics, and NSF/ANSI for cyst and total PFAS reduction

DOCUMENTS AND QUOTES

- Product page, photos and related models: aquelon.com/products/murdock-a132400s-vr
- Catalogues, certificates and installation guides: aquelon.com/library
- Priced quote within one working day: aquelon.com/quote · sales@aquelon.com · +971 4 501 1360 · WhatsApp +971 58 576 3023

Manufactured by Murdock. Supplied in the GCC by Aquelon. Data from the manufacturer's published documentation, issued 17 November 2026; confirm against the manufacturer's current data and drawings before construction or ordering. Source: Murdock manufacturer documentation